



HD Video Terminal

HD video conference terminal with MCU embedded software V2.3

NT90MT (Specification MT01M4)



Description

The brand-new integrated HD video conference terminal, featuring HD camera, exquisite appearance and excellent performance, supports H.265 technology and achieves UHD effects with ultra-low bandwidth. The simple installation method of the terminal makes it suitable for various small and medium conference venues.

Feature:

- * Adopt an integrated structure, built-in hardware video processing unit, HD camera, and embedded Linux operating system, non-Windows/Android operating system.
- * Support ITU-T H.323, SIP standard protocol, with good compatibility; support H.239, BFCP dual-stream protocol, the main and auxiliary streams can reach 1080P.
- * Support 64Kbps-8Mbps call bandwidth, support CIF, 4CIF, 720P, and 1080P video resolutions.
- * Support 1280*720 60fps/50fps/30fps/25fps, 1920*1080 60fps/50fps/30fps/25fps HD video signal input.
- * Support 1024*768 60fps, 1280*720 60fps, 1920*1080 60fps/30fps, 3840*2160 60fps/30fps HD video signal output.
- * Support H.261, H.263, H.263+, H.264, H.264 HP, H.265 video codec protocols, support G.711, G.722, G.722.1, G.722.1C, OPUS audio codec protocols, the sound quality is up to 48KHz.
- * Built-in MCU function module supports holding 4-party conferences, supports smooth extension to 8-party built-in MCU functions; supports built-in MCU holding mainstream and auxiliary conferences, and supports PC or mobile terminal joining the conference.
- * The terminal can be controlled by 2.4G remote, web, touch control, mouse and keyboard, etc.
- * Support freely turning on/off the remote video, support changing the window position of the video in the screen layout by drag and drop via the wireless mouse.
- * Adopt the B/S management structure, access the browser to log in to the WEB for remote management of the terminal, support Chinese and English language switching.
- * No need for registration, enter the meeting number to join the corresponding meeting, and you can choose the meeting interactive mode or live mode.
- * Support the chairman control mode. The chairman can control the dual-stream encoding rate, resolution and other parameters of all remote venues, and control the PTZ camera turning, focusing, and zooming operations.
- * The main screen supports 4K signal outputs, and a single screen supports actively opening up to 25 video images;
- * Support single-screen dual-display and dual-screen dual-display application functions, realize multi-screen layout, support multiple common layouts such as PIP; a single screen supports simultaneous display of 25 video images.
- * Support the wireless streaming function. Just install a software on the computer and connect it to the terminal through the network to realize the wireless shared streaming function; no need for external hardware devices.
- * Support full-screen display or composite display of auxiliary streams in the meeting.
- * Support the annotation function of the auxiliary stream, and make real-time annotations on the auxiliary stream screen when sending/receiving the auxiliary stream; set three different pen thicknesses, five pen colors, and set annotation graphics such as circles, squares, arrows, and lines. When sending auxiliary stream, you can set whether to enable annotation permissions for participants to make comments together.
- * Support controlling the dual-stream bandwidth of all remote venues, and support PTZ control.
- * Support controlling the speech of other terminals in the same meeting.
- * Equipped with a USB port to connect USB storage devices; support meeting recording function, to directly record video and audio during the meeting; support program upgrades and capture data packets through USB storage devices.
- * Support one-click meeting initiation on the terminal to quickly create a virtual meeting on the MCU and automatically join the meeting; support inviting venues to join the meeting on the terminal. The meeting supports functions such as electronic whiteboard, file sharing, electronic voting, and meeting sign-in.
- * Support scheduling meetings on APP, select participants, set meeting password, chairman password, live broadcast password, meeting time, etc. After submission, the MCU will automatically hold a meeting according to the timetable. The meeting supports functions such as electronic whiteboard, file sharing, electronic voting, meeting sign-in.
- * Support the chairman switching other terminals in the meeting between live mode and meeting mode on the APP. The meeting mode supports functions such as electronic whiteboard, file sharing, electronic voting, and meeting sign-in.
- * Support terminals actively applying to the chairman to switch from live mode to meeting mode. And they can switch to meeting mode with approval. The meeting mode supports functions such as electronic whiteboard, file sharing, electronic voting, and meeting sign-in.
- * Support the video polling function, you can choose the polling window, polling interval, and polling participant; support the voice activation function, you can set the voice activation window, and the venue with the loudest speech will automatically switch to this window.
- * Support Auto split screen function, automatically select the appropriate layout according to the number of terminals joining the meeting and automatically turn on the screen; support Autofill function, select a fixed screen layout, and automatically open it on an idle window after the terminal joins the meeting.
- * Support third-party systems to call the terminal through API to adjust cameras, send scrolling messages, set banners, switch screen layouts, and control the speech permission at each venue.
- * Support 1 HDMI input port, 2 HDMI output ports, 3 audio input ports (2*3.5mm, 1*HDMI), 2 audio output ports (1*HDMI, 1*3.5mm).
- * Integrated camera hardware design, built-in camera 12x optical zoom, 1080P full HD resolution.



HD Video Terminal

HD video conference terminal with MCU embedded software V2.3

NT90MT (Specification MT01M4)

Feature:

- * Support IP network packet loss repair mechanism; under 30% packet loss rate, the sound is continuous and the video is smooth, without lagging and blurring; under 80% packet loss rate, the sound is clear and can be accurately understood.
- * Super network adaptability, automatically adjust the resolution according to the network to ensure the smoothness of the meeting.
- * Support the banner function: you can add a banner on the screen, and set whether to enable the banner and the font size, font color, and background color of the banner.
- * Support scrolling message function: you can send scrolling message, and set whether to enable scrolling message and the font size, font color, background color and scrolling times of the scrolling message.
- * Support echo cancellation, noise suppression, mute detection, automatic gain function, support 20KHz broadband voice or higher.
- * Support inviting to join the meeting, you can view the real-time status of the online address book, and the online and offline status of each venue.
- * Support applying for speaking: apply to the chairman venue for speaking permission.
- * Support the venue Mute and Silence function, and the audio output of the venue is adjustable.
- * Support voice priority, support QOS strategy mode.
- * Support IPV4 and IPV6 protocols, support NAT traversal, and support the ability to cross routers and firewalls to ensure system security.
- * Support convenient management and maintenance, support local audiovisual loop diagnostic functions, and one-key local audiovisual testing, support network ping test on the operation interface, and support call log and historical record query.
- * Support viewing the media information of audio, mainstream video, and auxiliary video, including the protocol, format, bit rate, packet quantity, packet capacity, packet loss rate, packet loss quantity, jitter, delay, sending/receiving address, encrypted or not.
- * Support the web interactive whiteboard function, you can perform the whiteboard operation on the terminal control web, set three different pen thicknesses, five pen colors, and set annotation graphics such as circles, squares, arrows, and lines, set a solid color background or picture background; when the electronic whiteboard is operated on the web, the terminal output screen synchronously displays the whiteboard content. The electronic whiteboard supports paging function, up to 5 pages.
- * Support setting the delay of live broadcast, including 3 grades: smooth, moderate, and real-time.

Specification:

Model	NT90MT
Built-in MCU	4 bits
Video input	1 HDMI video input port + 1 built-in HD camera input
Video output	2 HD video output ports, HDMI*2
Audio input	3 audio input ports, MIC IN*1, LINE IN*1, HDMI*1
Audio output	2 audio output ports, HDMI*1, LINE OUT*1
Network port	1 Gigabit Ethernet port, RJ45*1; WIFI*1 (optional 4G network)
USB port	2 USB2.0 ports, used for device extensions or online upgrades
Display method	Support 4:3 and 16:9
Built-in camera	1/2.3-inch 12 million image sensor, 12× optical zoom, 1080P full HD resolution, 72.5° horizontal viewing angle
Ambient temperature	0°C~35°C (working state), -40°C~55°C (non-working state)
Relative humidity	10%~80% (working state), 0%~95% (non-working state) (no condensation)
Dimension	248×154×190mm
Power supply	DC 12V