

## ML1050STi

Ultra-compact short throw LED projector



- **HD Ready and LED technology** - Great for movies, gaming and PC-free presentations
- **Short throw lens with auto focus**
- **Feature packed** - Built-in media player, optional wireless, HDMI, microSD and built-in speaker
- **Ultra compact and lightweight** - only 420g

The ML1050STi is a compact and versatile projector designed for various scenarios. Whether you're in a business meeting, presenting on-the-go, or enjoying movies at home, this tiny powerhouse weighs just 420g and comes with a convenient carry bag.



## Specifications

EAN: 5055387668317, Colour: White+Gray

UPC: 796435 44 744 1, Colour: White+Gray



### Display/image

Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	1000/535
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	90%
Screen size	1.27m ~ 2.54m (50" ~ 100") diagonal

### Lamp info

Light source type	LED
LED life	20,000 hours

### Optical

Throw ratio	0.8:1
Projection distance (m)	0.86m - 1.72m
Zoom type	Fixed
Focal length (mm)	8.02mm/0.32"
Native offset	100%

### Connectivity

Connections	<b>Inputs</b> 1 x HDMI 1.4b, 1 x microSD card, 1 x USB-A reader <b>Outputs</b> 1 x Audio 3.5mm <b>Control</b> 1 x RS232 (via mini USB connector)
-------------	--

### General

Noise level (min)	22dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
24/7 operation	Yes
Operating conditions	0°C~40°C/41°F~95°F, max altitude 2500M/8202.5ft, max humidity 85%
Remote control	Card style
Speaker count	1
Watts per speaker	2W
In the box	Carry bag Universal I/O cable AC power cord Remote control 1x CR2032 Battery Basic user manual 1x RS232 Mini-USB adaptor
Operating system compatibility	Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+
Input lag	16.00ms
Optional wireless models	EZC-USB

### Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	23W
Power consumption (max)	67W

### Weight and dimensions

Dimensions (W x D x H) mm	112 x 123 x 57
Gross weight	1.2 kg
Net weight	0.4 kg

