



kramer

TBUS-6xl

Table Mount Modular Multi-Connection
Solution – Manually Retracting Lid



The TBUS-6xl is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately



FEATURES

Inner Frame - 3 different "T6F" inner frame options are available

Power Sockets - 8 different "TS" single power socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket

Optional Accessories - TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available

Retractable Lid - Manually slides into unit

Connector Depth - Adjustable

Installation Requirement - Table cutout of 225mm x 123mm (8.87" x 4.85")

Dimensions - Top plate: 24.3cm x 14.0cm (9.6" x 5.5") W, D; Enclosure: 22.1cm x 10.2cm x 13.0cm (8.7" x 4.0" x 5.1") W, D, H

Weight - 1.35 kg (2.8 lbs) approx.; table clamps: 0.25 kg (0.6 lbs) approx



kramer

TECHNICAL SPECIFICATIONS

INCLUDED ACCESSORIES: Power cord, table clamps, self locking ties, template, template screws

OPTIONS: Insert kit

Product Dimensions 24.30cm x 13.40cm x 14.00cm (9.57" x 5.28" x 5.51") W, D, H

Product Weight 1.7kg (3.8lbs) approx

Shipping Dimensions 36.00cm x 26.50cm x 21.00cm (14.17" x 10.43" x 8.27") W, D, H

Shipping Weight 2.6kg (5.7lbs) approx



kramer

CONFIGURATIONS

| | |
|--------------|---|
| TBUS-6xI(B) | Enclosure - Black Sand Blasted Anodized Aluminum Top |
| TBUS-6xI(BC) | Enclosure - Silver Sand Blasted Anodized Aluminum Top |

